



Technomelt Supra

High-performance hotmelt range for your packaging applications.

- » **High-quality results**
- » Excellent bond strength
- » Less maintenance effort, less downtimes thanks to extremely thermostable adhesive formulations
- » Average consumption up to 30% lower than conventional hotmelts
- » Outstanding cold flexibility and heat resistance

Technomelt Supra

High-performance hotmelt range for your packaging applications.

The Technomelt Supra range from Henkel with its powerful specialty adhesives is the product family that sets benchmarks in the adhesives industry when it comes to meeting your special needs regarding bond strength, mileage, application costs, and safety.

- » Higher mileage
- » Clean processing
- » Less maintenance
- » Shorter downtimes
- » Less waste
- » Less complexity
- » Resource-conserving adhesive solution

 Standard solutions	Application:	Viscosity: <i>Brookfield (at 160°C)</i>	Open time:	Optimal processing temperature
Technomelt Supra 100	Multi-purpose	1200 - 1600 mPas	Short to medium	160 - 190°C
Technomelt Supra 120	Fast setting and low viscosity	450 - 800 mPas	Short to medium	140 - 180°C
 Plus solutions	Application:	Viscosity: <i>Brookfield (at 160°C)</i>	Open time:	Optimal processing temperature
Technomelt Supra 100 Plus-22	Multi-purpose, fast setting, excellent machinability	1000 - 1700 mPas	Short to medium	160 - 190°C
Technomelt Supra 145 Plus	Multi-purpose, high thermal stability, good cold flexibility and excellent mileage	1150 - 1700 mPas	Short to medium	150 - 190°C
Technomelt Supra 150 Plus	High heat resistance and hot tack	1900 - 2500 mPas	Short to medium	160 - 190°C
Technomelt Supra 255 Plus 	Highest heat resistance, wide operating window	2200 - 2800 mPas	Short	160 - 190°C
 Cool solutions	Application:	Viscosity: <i>Brookfield</i>	Open time:	Optimal processing temperature
Technomelt Supra 100 Cool 	Lowest application temperature, fast setting	1000 - 1500 mPas <i>(at 100°C)</i>	Short	100 - 125°C
Technomelt Supra 130 Cool	Low application temperature, fast setting	1100 - 1200 mPas <i>(at 130°C)</i>	Short	130 - 150°C
 Specialties	Application:	Viscosity: <i>Brookfield (at 160°C)</i>	Open time:	Optimal processing temperature
Technomelt Supra 300 HT	Deep-freeze applications	1400 - 1800 mPas	Medium	160 - 190°C
Technomelt Supra 325 HT	High adhesion and long open time	1800 - 2600 mPas	Medium to long	160 - 190°C
Technomelt Supra 350 HT	High adhesion	1900 - 2600 mPas	Medium	160 - 190°C

Try Technomelt Supra now!

To experience how our Technomelt Supra range can improve your packaging operation, please contact your local sales representative for more information and assistance with product trials.

Distributed by:

Direct Adhesives Limited

Unit 15 Chartmoor Road
Leighton Buzzard
LU7 4WG
UK

Phone: 0800 085 7548

info@directadhesives.co.uk
www.directadhesives.co.uk

