



Technomelt EM

High-performance adhesive range for PET labeling.
Complete range of pressure sensitive adhesives.

- » **Easy, efficient, economical and reliable in operation**
- » Delivering top quality labeling
- » Versatile usage
- » High-performance in a wide variety of applications



Technomelt EM

High-performance adhesive range for PET labeling.

Rubber-based labeling hotmelts	Technomelt EM 357	Technomelt EM 360	Technomelt EM 362	Technomelt EM 132-22
Application:	standard	difficult substrates, hot filling, lowest migration tendency	standard, high elongation capacity	superior, low mileage, versatile
Viscosity: <i>Brookfield at 150°C</i>	600 - 150 mPas	850 - 1 400 mPas	600 - 1 050 mPas	300 - 500 mPas
Recommended application temperature:	130 - 150°C	140 - 180°C	130 - 150°C	120 - 140°C

EVA-based labeling hotmelts	Technomelt EM 349	Technomelt EM 300
Application:	basic, standard requirements (<i>up to 45°C</i>), low migration tendency	standard, for cold and hot containers (<i>up to 50°C</i>), lowest migration tendency
Viscosity: <i>Brookfield at 150°C</i>	1 000 - 2 000 mPas	1 500 mPas
Recommended application temperature:	130 - 160°C	130 - 160°C

Labeling hotmelt specialties	Technomelt EM 369	Technomelt EM 325/328	Technomelt EM 1051 E	Technomelt EM 89 E
Application:	labeling followed by head shrink (<i>contoured containers</i>)	suitable for PET recycling (<i>caustic soda dispersible</i>)	standard, spin spray applications, high elongation capacity	superior, water clear, trouble shooter for difficult surfaces
Viscosity: <i>Brookfield at 150°C</i>	1 350 - 2 050 mPas (<i>at 120°C</i>)	300 - 600 mPas (<i>at 150°C</i>)	1 300 mPas (<i>at 150°C</i>)	750 - 1 050 mPas (<i>at 130°C</i>)
Recommended application temperature:	110 - 150°C	120 - 160°C	150 - 160°C	120 - 140°C

Try Technomelt EM now!

To experience how our Technomelt EM range can improve your labeling operation, please contact your local sales representative for more information and assistance with product trials.

Distributed by:

Direct Adhesives Limited

Unit 15 Chartmoor Road
Leighton Buzzard
LU7 4WG
UK

Phone: 0800 085 7548

info@directadhesives.co.uk
www.directadhesives.co.uk

